



# TECHNICAL DATA SHEET



## DISC BRAKE SQUEAL FREE PART NO. 49661 (118mL)

### DESCRIPTION

DynaGrip® Disc Brake Squeal Free forms a water resistant, high-temperature film that absorbs noise while quieting squeaks and squeals. Specially formulated to dampen the vibrations that cause brake noise. For use on the back of non-shimmed disc pads.

### FEATURES

- Compatible with anti-lock brake systems
- Eliminates disc brake squeal
- Protects against corrosion
- Allows for easy disassembly
- For use on all cars and trucks

### TYPICAL APPLICATIONS

- Backing plates
- Brake pad contact points
- Disc brake pads
- Outboard and inboard pads for disc braking systems

### DIRECTIONS

- 1.Ensure the back of the pad is clean and dry.
- 2.Apply DynaGrip® Disc Brake Squeal Free liberally to the STEEL side of each outer pad.
- 3.Spread evenly over the entire surface of the pad.  
**DO NOT ALLOW CONTACT WITH THE PAD LINING.**
- 4.Apply 1 application width to the centre of the inside pad.
- 5.Allow 10 minutes for the product to set and fit pads. DynaGrip® Disc Brake Squeal Free will remain tacky.
- 6.Replace cap and store in a safe place **OUT OF REACH OF CHILDREN**



### PHYSICAL PROPERTIES

Colour/Appearance.....	Red Paste
Odour.....	Acrylic
Specific Gravity.....	1.0487
VOC %.....	Not Determined
Vapour Pressure.....	N/A
Evaporation Rate .....	Not Determined
Flammable.....	No
Plastic Safe.....	Not Determined
Flash Point.....	None
Removal.....	Remove with a degreaser or brake cleaner product

## TYPICAL CURING PERFORMANCE

**DynaGrip®** Disc Brake Squeal Free should dry for a minimum of 10 minutes prior to reassembly. Full dry time is three hours. Cure times will vary with temperature, humidity and gap.

## STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 32°C (90°F), **DynaGrip®** Disc Brake Squeal Free has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright. **DO NOT** stack cartons on their side. **NEVER** stack cartons more than 8 high. **DO NOT** store within 1 metre (4 feet) of roofline of the warehouse or storage building..

## GENERAL INFORMATION

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The user's exclusive remedy and the supplier's sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.

**QUALITY PRODUCTS**



**DynaGrip®** is a registered trademark of

AFC International Pty Ltd.  
21- 23 Hobart Street  
Riverstone NSW 2765  
TEL +61 2 9627 7125  
[www.dynagrip.com.au](http://www.dynagrip.com.au)