



SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.03.2016

Revision: 30.03.2016

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: DYNAGRIP DYNASTEEL CONCRETE REPAIR EPOXY PUTTY 56gm - 16402

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Sealants and adhesives

Details of Manufacturer or Importer:

AFC International Pty Ltd
21-23 Hobart Street
Riverstone NSW 2765

Phone Number: +61 2 9627 7125

Emergency telephone number: +61 2 9627 7125

2. HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2A	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.

Signal Word Warning

Hazard Statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.03.2016

Revision: 30.03.2016

Product Name: DYNAGRIP DYNASTEEL CONCRETE REPAIR EPOXY PUTTY 56gm - 16402

(Contd. of page 1)

P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.
P391	Collect spillage.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national regulations.

3 . COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

14807-96-6	Talc (Mg3H2(SiO3)4)	30-60%
1317-65-3	Limestone	10-30%
	⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane	10-30%
	⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
13463-67-7	Titanium oxide (TiO2)	1-5%
14808-60-7	Quartz (SiO2)	0.1-1%

4 . FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

Ingestion:

If swallowed, do not induce vomiting. Do not give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation and redness. May cause an allergic skin reaction.

Eye Contact: Causes eye irritation, redness, watering and pain.

Ingestion: Irritating to mouth, throat and stomach.

5 . FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Use fire extinguishing methods suitable to surrounding conditions.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon and sulfur, halogenated compounds and metal oxide/oxides.

(Contd. on page 3)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.03.2016

Revision: 30.03.2016

Product Name: DYNAGRIP DYNASTEEL CONCRETE REPAIR EPOXY PUTTY 56gm - 16402

(Contd. of page 2)

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 . ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment and Emergency Procedures:**

Wear approved dust/particulate filter respirator and full protective clothing. Evacuate all non-essential personnel from affected area. Do not breathe dust. Ensure adequate ventilation. Avoid generating dust. Do not touch or walk through spill material.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a closed, labeled waste container. Do not dry sweep.

7 . HANDLING AND STORAGE**Precautions for Safe Handling:**

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of dust. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Contaminated work clothing must not be allowed out of the workplace. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Protect from direct sunlight. Do not store above 35 °C. Keep in original container tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers.

8 . EXPOSURE CONTROLS AND PERSONAL PROTECTION**Exposure Standards:****14807-96-6 Talc (Mg₃H₂(SiO₃)₄)**NES | TWA: 2.5 mg/m³**13463-67-7 Titanium oxide (TiO₂)**NES | TWA: 10 mg/m³**1317-65-3 Limestone**

EH40/2005 WELs (United Kingdom (UK), 12/2011).

TWA 10 mg/m³ 8 hours. Form: inhalable dustTWA 4 mg/m³ 8 hours. Form: respirable dust**14808-60-7 Quartz (SiO₂)**NES | TWA: 0.1 mg/m³
respirable dust**Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapour below occupational exposure standards.

(Contd. on page 4)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.03.2016

Revision: 30.03.2016

Product Name: DYNAGRIP DYNASTEEL CONCRETE REPAIR EPOXY PUTTY 56gm - 16402

(Contd. of page 3)

Respiratory Protection:

Where an inhalation risk exists, wear a Class P1 (particulate) respirator. At high dust levels, wear a powered air purifying respirator (PAPR) with Class P3 (Particulate) filter or an air-line respirator or a full-face Class P3 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

PVC, PVA, nitrile, neoprene, rubber or vinyl gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information.

When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form:	Solid
Colour:	White-gray
Odour:	Strong, pungent (sulphurous)
Odour Threshold:	No information available
pH-Value:	Not applicable.
Melting point/Melting range:	No information available
Initial Boiling Point/Boiling Range:	No information available
Flash Point:	>93.3 °C
Flammability:	Product does not sustain combustion.
Auto-ignition Temperature:	No information available
Decomposition Temperature:	>220 °C
Explosion Limits:	
Lower:	No information available
Upper:	No information available
Vapour Pressure:	No information available
Relative Density at 20 °C:	2.03
Vapour Density:	Not applicable.
Evaporation Rate:	Not applicable
Solubility in Water:	Insoluble in cold water and hot water.
Solubility in Solvents:	Easily soluble in methanol and acetone.
Partition Coefficient (n-octanol/water):	No information available
Viscosity:	Not applicable

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: No further relevant information available.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Direct sunlight.

Incompatible Materials: No further relevant information available.

(Contd. on page 5)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.03.2016

Revision: 30.03.2016

Product Name: DYNAGRIP DYNASTEEL CONCRETE REPAIR EPOXY PUTTY 56gm - 16402

(Contd. of page 4)

Hazardous Decomposition Products:

Oxides of carbon and sulfur, halogenated compounds and metal oxide/oxides.

11 . TOXICOLOGICAL INFORMATION**Toxicity:****LD₅₀/LC₅₀ Values Relevant for Classification:****13463-67-7 Titanium oxide (TiO₂)**

Oral	LD ₅₀	>20000 mg/kg (rat)
Dermal	LD ₅₀	>10000 mg/kg (rabbit)
Inhalation	LC ₅₀ /4 h	>6.82 mg/l (rat)

1317-65-3 Limestone

Oral	LD ₅₀	6450 mg/kg (rat)
------	------------------	------------------

Acute Health Effects**Inhalation:** May cause respiratory irritation.**Skin:**

Causes skin irritation and redness. May cause an allergic skin reaction. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Eye: Causes eye irritation, redness, watering and pain.**Ingestion:** Irritating to mouth, throat and stomach.**Skin Corrosion / Irritation:** Causes skin irritation.**Serious Eye Damage / Irritation:** Causes serious eye irritation.**Respiratory or Skin Sensitisation:** May cause an allergic skin reaction.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Talc not containing asbestos or asbestiform fibres is classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

Titanium dioxide is classified by IARC as Group 2B - Possibly carcinogenic to humans.

Silica dust, crystalline, in the form of quartz or cristobalite is classified by IARC as Group 1 - Carcinogenic to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:** May cause respiratory irritation.**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:**

The prolonged and repeated exposure (by inhalation) to respirable (crystalline) silica cause silicosis, a debilitating lung disease. The crystalline silica dust is practically insoluble in body fluids and can be deposited in lungs. Cigarette smoking can reduce the clearance of crystalline silica. The data indicate that the relative lung cancer risk is increased for people with silicosis.

Existing Conditions Aggravated by Exposure: No information available**12 . ECOLOGICAL INFORMATION****Ecotoxicity:** No information available

(Contd. on page 6)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.03.2016

Revision: 30.03.2016

Product Name: DYNAGRIP DYNASTEEL CONCRETE REPAIR EPOXY PUTTY 56gm - 16402

(Contd. of page 5)

Aquatic toxicity:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and Degradability: No information available**Bioaccumulative Potential:** No information available**Mobility in Soil:** No information available**Other adverse effects:** No information available**13 . DISPOSAL CONSIDERATIONS****Disposal Methods and Containers:** Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

14 . TRANSPORT INFORMATION**UN Number****ADG****IMDG**

Not regulated

UN3077

Proper Shipping Name**ADG****IMDG**

Not regulated

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
SOLID, N.O.S.**Dangerous Goods Class****ADG Class:****IMDG Class:**

Not regulated

9 Miscellaneous dangerous substances and articles.

Packing Group:**ADG****IMDG**

Not regulated

III

Marine pollutant:

Symbol (fish and tree)

EMS Number:

F-A,S-F

Hazchem Code:

2Z

Special Provisions:

179, 274, 331, 335, AU01

Limited Quantities:

5 kg

Packagings & IBCs - Packing Instruction:

P002, IBC08, LP02

Packagings & IBCs - Special Packing Provisions: PP12, B3**Portable Tanks & Bulk Containers - Instructions:** T1, BK2**Portable Tanks & Bulk Containers - Special Provisions:**

TP33

15 . REGULATORY INFORMATION**Australian Inventory of Chemical Substances:**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
13463-67-7	Titanium oxide (TiO ₂)
1317-65-3	Limestone

(Contd. on page 7)

SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.03.2016

Revision: 30.03.2016

Product Name: DYNAGRIP DYNASTEEL CONCRETE REPAIR EPOXY PUTTY 56gm - 16402

(Contd. of page 6)

25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
14808-60-7	Quartz (SiO ₂)

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:
Not Scheduled.

16 . OTHER INFORMATION

Date of Preparation or Last Revision: 30.03.2016

Prepared by: MSDS.COM.AU Pty Ltd

www.msds.com.au

Abbreviations and acronyms:

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percent

LD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Skin sensitisation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term (Chronic). Category 2

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011"

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. AFC International Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.